

2M Series Performance Specifications

Materials and Finishes



PERFORMANCE SPECIFICATIONS	
Current Rating (Maximum)	Size #23 contact: 5 AMPS. Size #20 contact: 7.5 AMPS. Size #16 contact: 13 AMPS. Size #12 contact: 23 AMPS.
Test Voltage (Dielectric Withstanding Voltage) Mated Connectors	Size #23 contacts: 750 VAC RMS sea level, 400 VAC RMS 40,000 feet Size #20 contacts: 1000 VAC RMS sea level, 400 VAC RMS 40,000 feet Size #20HD contacts: 1000 VAC RMS sea level, 400 VAC RMS 40,000 feet Size #16 contacts: 1800 VAC RMS sea level, 1000 VAC RMS 40,000 feet Size #12 contacts: 1800 VAC RMS sea level, 1000 VAC RMS 40,000 feet
Insulation Resistance	5000 megohms minimum
Contact Resistance	Size #23 contact: 73 millivolt drop at 5 AMPS. test current Size #20 contact: 55 millivolt drop at 7.5 AMPS. test current Size #16 contact: 49 millivolt drop at 13 AMPS. test current Size #12 contact: 42 millivolt drop at 23 AMPS. test current
Operating Temperature	-65° C. to +175° C.
Immersion, Mated	1 meter water immersion for 1 hour (2M803 Series splash proof only)
Magnetic Permeability	2.0 μ maximum

MATERIALS AND FINISHES	
Aluminum Shell, Barrel, and Coupling Nut	Aluminum alloy 6061 T6
Stainless Steel Shell, Barrel Coupling Nut	Passivated Stainless Steel, 200° C
Front and Rear Inserts	Polyphenylene Sulfide (PPS)
Contact Retention Clip	Beryllium copper, heat-treated
Grommet, Peripheral Seal and Interfacial Seal	Fluorosilicone Rubber
Contacts	Gold Plated Copper alloy
Socket Contact Hood	Passivated Stainless steel
Adhesives	Various Epoxies & RTV's
Potting Compound, PCB and Solder Cup Versions	High Strength Epoxy

Please refer to the comprehensive 2M Series Product Specification for additional parameters and test methods.
Filter and Hermetic designs have different specifications. (Please refer to individual sections)

Contact Amphenol Aerospace for more information at 800-678-0141 • www.amphenol-aerospace.com

2M Series Performance Specifications

Complete Product Specifications

DESCRIPTION	REQUIREMENT	PROCEDURE																											
ELECTRICAL																													
Contact resistance	SAE AS39029 Table V <table><tr><td>Wire Size</td><td>Test Current</td><td>Max Voltage Drop</td></tr><tr><td>12</td><td>23</td><td>42</td></tr><tr><td>14</td><td>17</td><td>40</td></tr><tr><td>16</td><td>13</td><td>49</td></tr><tr><td>20</td><td>7.5</td><td>55</td></tr><tr><td>22</td><td>5</td><td>73</td></tr><tr><td>24</td><td>3</td><td>45</td></tr><tr><td>26</td><td>2</td><td>52</td></tr><tr><td>28</td><td>1.5</td><td>54</td></tr></table>	Wire Size	Test Current	Max Voltage Drop	12	23	42	14	17	40	16	13	49	20	7.5	55	22	5	73	24	3	45	26	2	52	28	1.5	54	EIA-364-06 Test current in amperes. Voltage drop in millivolts. Silver-coated copper wire, +25°C.
Wire Size	Test Current	Max Voltage Drop																											
12	23	42																											
14	17	40																											
16	13	49																											
20	7.5	55																											
22	5	73																											
24	3	45																											
26	2	52																											
28	1.5	54																											
Low level contact resistance	<table><tr><td>Wire Size</td><td>Max. Milliohms</td></tr><tr><td>16</td><td>5</td></tr><tr><td>20</td><td>9</td></tr><tr><td>22</td><td>15</td></tr><tr><td>24</td><td>20</td></tr><tr><td>26</td><td>31</td></tr><tr><td>28</td><td>50</td></tr></table>	Wire Size	Max. Milliohms	16	5	20	9	22	15	24	20	26	31	28	50	EIA-364-23 100 milliamperes maximum and 20 millivolts maximum open circuit voltage													
Wire Size	Max. Milliohms																												
16	5																												
20	9																												
22	15																												
24	20																												
26	31																												
28	50																												
Insulation resistance	5000 megohms minimum	EIA-364-21 500 volts DC ± 50 volts. Test between adjacent contacts and contacts to shell.																											
Dielectric withstanding voltage, sea level	No breakdown or flashover #23 contacts 750 volts #20HD contacts 750 volts #16 contacts 1800 volts #12 contacts 1800 volts	EIA-364-20 AC RMS 60 Hz. One minute dwell. Unmated or mated																											
Dielectric withstanding voltage, 40,000 feet altitude	No breakdown or flashover #23 contacts 100 volts #20HD contacts 150 volts #16 contacts 1000 volts #12 contacts 1000 volts	EIA-364-20 AC RMS 60 Hz. One minute dwell. mated condition																											
Current carrying capacity	<table><tr><td>Contact Size</td><td>Max Current</td></tr><tr><td>12</td><td>23</td></tr><tr><td>16</td><td>13</td></tr><tr><td>20</td><td>7.5</td></tr><tr><td>23</td><td>5</td></tr></table>	Contact Size	Max Current	12	23	16	13	20	7.5	23	5	EIA-364-70 Method 1																	
Contact Size	Max Current																												
12	23																												
16	13																												
20	7.5																												
23	5																												

Please refer to the comprehensive 2M Series Product Specification for additional parameters and test methods.
Filter and Hermetic designs have different specifications. (Please refer to individual sections)

Contact Amphenol Aerospace for more information at 800-678-0141 • www.amphenol-aerospace.com

2M Series Performance Specifications

Complete Product Specifications



DESCRIPTION	REQUIREMENT	PROCEDURE																																
Shell-to-shell conductivity, Initial	The maximum voltage drop across a mated pair shall not exceed the values shown. <table><thead><tr><th>Series</th><th>Voltage Drop</th></tr></thead><tbody><tr><td>2M801</td><td>2.5</td></tr><tr><td>2M803</td><td>100</td></tr><tr><td>2M804</td><td>2</td></tr><tr><td>2M805</td><td>2</td></tr></tbody></table>	Series	Voltage Drop	2M801	2.5	2M803	100	2M804	2	2M805	2	EIA-364-83 Electroless Nickel Plated Connectors																						
Series	Voltage Drop																																	
2M801	2.5																																	
2M803	100																																	
2M804	2																																	
2M805	2																																	
Shell-to-shell conductivity, after conditioning (48 hours salt spray)	The maximum voltage drop across a mated pair shall not exceed the values shown. <table><thead><tr><th>Series</th><th>Voltage Drop</th></tr></thead><tbody><tr><td>2M801</td><td>2.5</td></tr><tr><td>2M803</td><td>200</td></tr><tr><td>2M804</td><td>4</td></tr><tr><td>2M805</td><td>2</td></tr></tbody></table>	Series	Voltage Drop	2M801	2.5	2M803	200	2M804	4	2M805	2	EIA-364-83 Electroless Nickel Plated Connectors																						
Series	Voltage Drop																																	
2M801	2.5																																	
2M803	200																																	
2M804	4																																	
2M805	2																																	
Shielding effectiveness, low frequency (100MHz-1000 MHz)	<table><thead><tr><th></th><th colspan="3">dB Min. Attenuation</th></tr><tr><th>Frequency</th><th>Series 2M801</th><th>Series 2M803</th><th>Series 2M804, 2M805</th></tr></thead><tbody><tr><td>100 MHz</td><td>75</td><td>60</td><td>90</td></tr><tr><td>200 MHz</td><td>70</td><td>55</td><td>88</td></tr><tr><td>300 MHz</td><td>65</td><td>55</td><td>88</td></tr><tr><td>400 MHz</td><td>63</td><td>50</td><td>87</td></tr><tr><td>800 MHz</td><td>58</td><td>45</td><td>85</td></tr><tr><td>1000 MHz</td><td>55</td><td>40</td><td>85</td></tr></tbody></table>		dB Min. Attenuation			Frequency	Series 2M801	Series 2M803	Series 2M804, 2M805	100 MHz	75	60	90	200 MHz	70	55	88	300 MHz	65	55	88	400 MHz	63	50	87	800 MHz	58	45	85	1000 MHz	55	40	85	EIA-364-21 Electroless Nickel Plated Connectors
	dB Min. Attenuation																																	
Frequency	Series 2M801	Series 2M803	Series 2M804, 2M805																															
100 MHz	75	60	90																															
200 MHz	70	55	88																															
300 MHz	65	55	88																															
400 MHz	63	50	87																															
800 MHz	58	45	85																															
1000 MHz	55	40	85																															
Shielding effectiveness, high frequency (1GHz-10GHz)	<table><thead><tr><th></th><th colspan="2">dB Min. Attenuation</th></tr><tr><th>Frequency</th><th>Series 2M801, 2M804</th><th>Series 2M805</th></tr></thead><tbody><tr><td>1 GHz</td><td>55</td><td>85</td></tr><tr><td>3 GHz</td><td>50</td><td>69</td></tr><tr><td>5 GHz</td><td>45</td><td>66</td></tr><tr><td>19 GHz</td><td>40</td><td>65</td></tr></tbody></table>		dB Min. Attenuation		Frequency	Series 2M801, 2M804	Series 2M805	1 GHz	55	85	3 GHz	50	69	5 GHz	45	66	19 GHz	40	65	EIA-364-66 Electroless Nickel Plated Connectors														
	dB Min. Attenuation																																	
Frequency	Series 2M801, 2M804	Series 2M805																																
1 GHz	55	85																																
3 GHz	50	69																																
5 GHz	45	66																																
19 GHz	40	65																																

Please refer to the comprehensive 2M Series Product Specification for additional parameters and test methods.
Filter and Hermetic designs have different specifications. (Please refer to individual sections)

2M Series Performance Specifications

Complete Product Specifications

DESCRIPTION	REQUIREMENT	PROCEDURE
MECHANICAL		
Vibration, Sine	No discontinuity of greater than 1 microsecond, no cracking, breaking or loosening of parts, plug shall not become disengaged from receptacle. Connectors shall meet electrical requirements after vibration test.	MIL-STD-202 Method 204, test Condition G 12 sweep cycles per axes, 20 min. per 10-2000-10Hz @ temp. 2M801/2M805 - 60 g 2M803/2M804 - 30 g
Vibration, Random	No discontinuity of greater than 1 microsecond, no cracking, breaking or loosening of parts, plug shall not become disengaged from receptacle. Connectors shall meet electrical requirements after vibration test.	EIA-364-28 Test Condition V Letter I 100 milliamp test current 50- 2,000 Hz @ temp. 2M801/2M805 - 43.9 g RMS 2M803/2M804 - 37.80 g RMS
Gunfire Vibration	No discontinuity of greater than 1 microsecond, no cracking, breaking or loosening of parts, plug shall not become disengaged from receptacle. Connectors shall meet electrical requirements after vibration test.	MIL-STD-810F Method 519.5
Mechanical Shock	No discontinuity of greater than 1 microsecond, no cracking, breaking or loosening of parts, plug shall not become disengaged from receptacle. Connectors shall meet electrical requirements after shock test.	EIA-364-27 Condition D 300 G, halfsine, 3ms, 3 axes
Mechanical durability, at ambient temperature	No deterioration which will adversely affect the connector after 2000 cycles (where applicable) of mating and unmating. Connectors shall meet contact resistance, insulation resistance, shell-to-shell resistance, DWV, and mating and unmating force.	EIA-364-09
Solderability, PC tail contacts	95% solder coverage. Smooth, bright and even finish.	EIA-364-52 Category 3 8 hours steam aging prior to test 245° C, 4-5 sec. dwell 10X magnification
Resistance To Soldering Heat	No damage to connector. Connectors shall meet insulation resistance and waterproof sealing requirements.	EIA-364-56 260° C, 10 seconds (PC tail)

Please refer to the comprehensive 2M Series Product Specification for additional parameters and test methods.
Filter and Hermetic designs have different specifications. (Please refer to individual sections)

Contact Amphenol Aerospace for more information at 800-678-0141 • www.amphenol-aerospace.com

2M Series Performance Specifications

Complete Product Specifications



DESCRIPTION	REQUIREMENT	PROCEDURE																														
Impact	No impairment of function. Connector shall meet contact resistance, insulation resistance and waterproof sealing.	EIA-364-42 1 meter 8 drops																														
Contact retention	<table><tr><td>Contact Size</td><td>Min. Pounds</td><td>Min. Newtons</td></tr><tr><td>23</td><td>10</td><td>45</td></tr><tr><td>20</td><td>15</td><td>67</td></tr><tr><td>20HD</td><td>10</td><td>45</td></tr><tr><td>16</td><td>25</td><td>111</td></tr><tr><td>12</td><td>25</td><td>111</td></tr></table>	Contact Size	Min. Pounds	Min. Newtons	23	10	45	20	15	67	20HD	10	45	16	25	111	12	25	111	EIA-364-29												
Contact Size	Min. Pounds	Min. Newtons																														
23	10	45																														
20	15	67																														
20HD	10	45																														
16	25	111																														
12	25	111																														
Contact separation force	<table><tr><td>Contact Size</td><td>Min. Ounces</td><td>Min. Newtons</td></tr><tr><td>23</td><td>0.5</td><td>0.14</td></tr><tr><td>20</td><td>0.7</td><td>0.19</td></tr><tr><td>16</td><td>2.0</td><td>0.56</td></tr><tr><td>12</td><td>3.0</td><td>0.83</td></tr></table>	Contact Size	Min. Ounces	Min. Newtons	23	0.5	0.14	20	0.7	0.19	16	2.0	0.56	12	3.0	0.83	SAE AS39029															
Contact Size	Min. Ounces	Min. Newtons																														
23	0.5	0.14																														
20	0.7	0.19																														
16	2.0	0.56																														
12	3.0	0.83																														
Coupling torque	Threaded coupling connector coupling torque shall not exceed the following requirements. <table><tr><th colspan="2">Shell Size</th><th></th></tr><tr><th>Series 2M801</th><th>Series 2M805</th><th>Inch Pounds</th></tr><tr><td>5, 6, 7</td><td>8, 9</td><td>8</td></tr><tr><td>8, 9</td><td>10, 11</td><td>9</td></tr><tr><td>10</td><td>12</td><td>12</td></tr><tr><td>12, 13</td><td>15</td><td>16</td></tr><tr><td>14, 15</td><td>18</td><td>28</td></tr><tr><td>16, 17</td><td>19</td><td>24</td></tr><tr><td>21</td><td></td><td>32</td></tr><tr><td></td><td>23</td><td>36</td></tr></table>	Shell Size			Series 2M801	Series 2M805	Inch Pounds	5, 6, 7	8, 9	8	8, 9	10, 11	9	10	12	12	12, 13	15	16	14, 15	18	28	16, 17	19	24	21		32		23	36	
Shell Size																																
Series 2M801	Series 2M805	Inch Pounds																														
5, 6, 7	8, 9	8																														
8, 9	10, 11	9																														
10	12	12																														
12, 13	15	16																														
14, 15	18	28																														
16, 17	19	24																														
21		32																														
	23	36																														
Unmating force (Series 2M804)	Series 2M804 push/pull connectors <table><tr><th>Contact Arrangement</th><th>Pounds</th></tr><tr><td>5-3</td><td>10.6</td></tr><tr><td>6-4</td><td>10.8</td></tr><tr><td>6-7</td><td>11.4</td></tr><tr><td>7-10</td><td>12.0</td></tr><tr><td>8-13</td><td>12.6</td></tr><tr><td>9-19</td><td>13.8</td></tr><tr><td>10-26</td><td>15.2</td></tr><tr><td>12-37</td><td>17.4</td></tr><tr><td>14-55</td><td>21.0</td></tr></table>	Contact Arrangement	Pounds	5-3	10.6	6-4	10.8	6-7	11.4	7-10	12.0	8-13	12.6	9-19	13.8	10-26	15.2	12-37	17.4	14-55	21.0											
Contact Arrangement	Pounds																															
5-3	10.6																															
6-4	10.8																															
6-7	11.4																															
7-10	12.0																															
8-13	12.6																															
9-19	13.8																															
10-26	15.2																															
12-37	17.4																															
14-55	21.0																															

Please refer to the comprehensive 2M Series Product Specification for additional parameters and test methods.
Filter and Hermetic designs have different specifications. (Please refer to individual sections)

Perform Spec

Insert retention

Operating temperature

Water immersion, mated

Water immersion, open face
panel mount receptacles
with non-removable printed
circuit board or solder cup
contacts

Humidity, cyclic (damp heat, cyclic) (moisture resistance)

EIA-364-31 Condition B Method III
80-98% RH
10 cycles (10 days)
+25° C to +65° C
Step 7b vibration deleted.
24 hour recovery period.

B

2M Series Performance Specifications

Complete Product Specifications



DESCRIPTION	REQUIREMENT	PROCEDURE
21 day humidity (damp heat, long term)	No deterioration which will adversely affect the connector. Following the drying period, connectors shall meet 100 megohms minimum, contact resistance, shell-to-shell resistance, DWV, mating and unmating requirements.	EIA-364-31 Condition C Method II 90-95% RH 40° C Apply 100 volts DC during test. 4 hours drying time at ambient temperature prior to final measurements.
Thermal shock	No mechanical damage or loosening of parts. Following thermal shock, connector shall meet contact resistance, DWV, insulation resistance and shell-to-shell resistance requirements.	EIA-364-32 Test Condition IV 5 cycles consisting of -65° C 30 minutes, +25° C 5 minutes max., +150° C 30 minutes, +25° C 5 minutes max.
Corrosion (salt mist)	No exposure of base metal. Connectors shall meet DWV and contact resistance requirements following the test.	EIA-364-26 5% salt solution 35° C Unmated connectors Code C: 48 hours Code M: 48 hours Code MT: 500 hours Code NF: 500 hours Code 500 hours Code ZNU: 500 hours
Sand and dust	Mated connectors shall withstand the effects of blowing sand and dust	MIL-STD-810F, Method 510.4
Fungus	Connector materials shall be fungus inert.	MIL-STD-810F, Method 508.5
Fluid immersion	No visible damage from immersion in various fuels and oils. Connector shall meet coupling torque and dielectric withstanding voltage requirements.	EIA-364-10 Unmated connectors
Altitude immersion	No evidence of moisture on connector interface or contacts. Connector shall meet dielectric withstanding voltage.	EIA-364-03

Please refer to the comprehensive 2M Series Product Specification for additional parameters and test methods.
Filter and Hermetic designs have different specifications. (Please refer to individual sections)

Contact Amphenol Aerospace for more information at 800-678-0141 • www.amphenol-aerospace.com